

mahindra *Rise*

**A VEHICLE FOR LAST MILE
DELIVERY LIKE NEVER BEFORE.**

THE NEW ELECTRIC TREO ZOR.



TREO
Zor

**SAVINGS LIKE
NEVER BEFORE.**

**ADDITIONAL
₹1 00 000.00
PER YEAR.**

**INCREMENTAL SAVINGS
THAT NO DIESEL VEHICLE CAN MATCH
SAVINGS OF 2.0 / km ON FUEL.
MAINTENANCE OF 11 paise / km**



POWER TO MAKE MORE TRIPS. AND MORE PER TRIP.

**HIGHER POWER OF 8 kW
EXCELLENT TORQUE OF 42 Nm
HIGHEST-IN-CLASS PAYLOAD OF 550 kg
ADVANCED IP67 RATED MOTOR**



TECHNOLOGY THAT GOES THE DISTANCE, BATTERY THAT NEEDS NO MAINTENANCE.

ADVANCED ZERO MAINTENANCE LITHIUM-ION BATTERY
LONG BATTERY LIFE OF 1.5 Lakh km
3 years / 80000 km STANDARD WARRANTY



***DELIVER MORE
THAN BEFORE.***

***BUT WITH
LESS FATIGUE
THAN EVER
BEFORE.***

***CLUTCHLESS
DIRECT DRIVE TECHNOLOGY
NOISELESS
VIBRATION-FREE***



LOADS FASTER, UNLOADS FASTER, TO DO BUSINESS FASTER

**BEST-IN-CLASS* LOADING HEIGHT OF 675 mm.
CONVENIENT 3 WAY CARGO TRAY**



*WHEN COMPARED WITH ELECTRIC CARGO 3 WHEELERS

**FAR LONGER,
FAR MORE STABLE.
SO YOU AND
YOUR LOAD
REACH SAFER.**

LONGEST-IN-INDUSTRY* WHEELBASE : 2216 mm

LARGEST-IN-INDUSTRY* TYRES : 30.48 cm



MANAGE YOUR FLEET MORE EFFICIENTLY THAN EVER. USING THE NEMO APP.

*REAL TIME PERFORMANCE TRACKING
MONITORING OPERATIONS
DATA AND MACHINE LEARNING
AND MUCH MORE*



**A RANGE OF
VARIANTS TO
SUIT ALL
YOUR NEEDS.
LIKE NEVER
BEFORE.**



TREO
Zor DV

TREO
Zor

TREO
Zor FB

TECHNICAL SPECIFICATIONS

Variant:	Pickup	Flatbed	Delivery Van
Vehicle category	L5N	L5N	L5N
Vehicle roof type	Hard Panel	Hard Panel	Hard Panel
Payload-kg	550	578	500
Volume-m ³	NA	NA	3.4
Vehicle Dimensions & Height:			
Dimensions-Length x Width x Height-mm	3100 X 1460 X 1762	3100 X 1460 X 1762	3100 X 1460 X 2175
Wheelbase -mm	2236	2236	2236
Ground clearance-mm	123	123	123
Rear track-mm	1220	1220	1220
Turning radius-m	3.05	3.05	3.05
Vehicle kerb weight-kg	445	417	495
Vehicle GVW-kg	995	995	995
Tray Size Length x Width x Height (inside dimensions)-mm	1500 X 1400 X 270	1570 X 1460	NA
Box Size Length x Width x Height (inside dimensions)-mm	NA	NA	1564 X 1452 X 1484
Performance			
Top Speed km/h	50	50	50
Typical driving range-km	80	80	80
Gradeability-degree	7	7	7
Battery			
Battery type/Voltage-V	Lithium-Ion, 48 V	Lithium-Ion, 48 V	Lithium-Ion, 48 V
Battery capacity (Installed) - kWh	7.37	7.37	7.37
Charging time at standard conditions	3 h 50 min	3 h 50 min	3 h 50 min
Drivetrain			
Peak power-kW	8	8	8
Peak torque-Nm	42	42	42
Transmission type	Direct drive technology	Direct drive technology	Direct drive technology
Suspension & Brakes			
Suspension-Front	Hydral spring + Damper + Hydraulic shock absorber		
Suspension-Rear	Rigid axle with leaf spring		
Brakes Front/Rear	Hydraulic brake		
Working brake	Mechanical lever type		
Features			
Windscreen and Wiping system	✓	✓	✓
Spare wheel provision	✓	✓	✓
Driving modes - FNR (Forward, Neutral, Reverse)	✓	✓	✓
Economy and boost mode	✓	✓	✓
Lockable glove box	✓	✓	✓
12 V socket	✓	✓	✓
Telematics unit and GPS	✓	✓	✓
15 A off-board charger	✓	✓	✓
Hazard indicator	✓	✓	✓
Reverse buzzer	✓	✓	✓



TREO
Zor DV



TREO
Zor



TREO
Zor FB